

Andura Black Bitumen Paint

Description

Andura Black Bitumen Paint is a general-purpose bitumen paint suitable for brush application. It can be applied to a wide variety of surfaces including iron and steel, metal fabrications, castings, fibre reinforced cement, concrete and similar surfaces, to provide a weather-proof and corrosion resistant coating.

Product details

Container sizes 5 litre

Typical properties

Solid contents w/w	approx 50%
Coverage m ² /L/coat	
Metal surfaces	11
Porous surfaces	5
Relative density at 15°C	0.91 – 0.93
Drying time at 15°C	2 – 4 hours
Flash point (Abel closed cup) °C	minimum 32
Application temperature limit °C	4 – 40
Film thickness per coat at 11m ² /L mm	
Wet	0.1
Dry	0.05

Application

Surfaces onto which Andura Black Bitumen Paint is to be applied must be cleaned to remove all loose flaking paint, rust, dust or grease together with any other material which may affect adhesion. Where previously applied paints are sound and adhering well they need not be removed.

Ensure metal surfaces are adequately prepared before applying Andura Black Bitumen Paint. Bare metal should be primed with a suitable rust inhibitive primer and new galvanised surfaces degreased and painted with an etching primer, in accordance with the manufacturer's instructions.

Apply Black Bitumen Paint by brush, allowing a minimum of two coats. Each coat must be allowed to fully dry before over-coating.

Notes

In common with all bitumen paints, Andura Black Bitumen Paint weathers to a matt black finish, and cannot be over-coated with conventional oil based paints.

Do not apply to surfaces previously treated with a tar-based product.

Drying times may be extended during low temperatures.

Equipment Care

Brushes and tools can be cleaned in T66 Thinners.

Storage

Back Bitumen Paint contains a flammable solvent, and all normal precautions against fire must be taken during both storage and use. Storage in original containers in cool dry conditions. Keep away from sources of ignition.

Note: Always store and transport container in a secure upright position.

Shelf Life

Up to 2 years when stored as recommended.

Health & Safety

A Health and Safety data sheet relating to Andura Black Bitumen Paint is available from Andura Coatings Ltd.

Technical Support

Andura offers a comprehensive range of high performance coatings for the interior and exterior protection and decoration of building surfaces. Andura provides a support package to engineers, architects, specifiers, end-users and contractors as well as training and on-site assistance.

Quality Management

Andura is a British Standards approved firm and has been since 1992.

Andura's Quality Management Systems have been assessed and approved by BSI and conform to ISO 9001: 2008.

Disclaimer

The advice and information provided in this data sheet is given in good faith, but carries no guarantee or acceptance of responsibility. This data sheet becomes invalid as soon as a new edition has been issued. Please check with Andura Coatings that you have the latest edition.

Andura Coatings Limited
20 Murdock Road
Bicester
Oxon
OX26 4PP

Telephone: 01869 240374
Fax: 01869 240375
Web: www.andura.com
e-mail: info@andura.co.uk

Issue 07/05



Certificate No. FM 14830