

# ANDURA JOINT MASTIC

A superior exterior grade, flexible and paintable mastic sealant for sealing joints and gaps, such as around window and door frames.

## Instructions for Use

### Before you start

Wear suitable work clothes and thoroughly protect all surrounding areas. The joint or gap to be sealed should be clean and dry. Deep gaps should be filled to avoid using excessive amounts of sealant.

For neat, clean lines, use Masking Tape on both sides of the joint and remove immediately after smoothing the sealant.

### How to use

1. Cut off tip of cartridge above screw thread. Screw nozzle onto cartridge. Remove red nozzle overcap. Cut off tapered end of nozzle at a 45° angle to a width matching the gap to be sealed. To make use of resealable nozzle, do not cut below screw thread.
2. Insert into cartridge gun. Place nozzle at start of gap at an angle of approximately 30°. Squeeze gun trigger and push forward ensuring an even pressure along the gap to be sealed.
3. Smooth sealant with a wet round-ended spatula or similar tool within 5 minutes. Remove excess sealant before it dries with water.
4. Protect from water and damp conditions during drying process. If using indoors, ventilate surrounding areas to assist drying. Check sealant is fully dry before water contact.

DRYING TIME GUIDE		
	Dimensions	Approx drying time
Min bead size	6 mm wide x 3mm deep	24 hours
Max bead size	12 mm wide x 6mm deep	72 hours
Use of bead sizes outside these limits may lead to subsequent failure.		

5. To enable any sealant remaining in cartridge to be re-used, seal nozzle with red overcap. Contents can remain useable for up to six months depending on storage conditions.

### How much will it cover ?

Approximately 11m using a 6mm bead.

### Sensible Working Practices

Wash hands after use and before meals.

Wash splashes from skin, clothing and other surfaces immediately with water.

In case of contact with eyes, wash immediately with plenty of water.

Keep out of the reach of children and animals.

### What to avoid

Do not use in permanently wet areas.

Do not use below 5°C.

Drying time will be extended in cold or damp conditions. If using outdoors, do not apply in wet or damp conditions, e.g. when rain or snow are imminent. For use as a building sealant only.

### Guarantee

Guarantee is limited to refund of product cost only. This does not affect your statutory rights.

**This product should be used in accordance with the manufacturer's instructions.**

For further technical information and practical advice not covered on the pack call 01869 240374.

### Quality Management

Andura is a British Standards approved firm and has been since 1992.

Andura's Quality Management Systems have been assessed and approved by BSI and conform to ISO 9001: 2008.

## Disclaimer

The advice and information provided in this data sheet is given in good faith, but carries no guarantee or acceptance of responsibility. This data sheet becomes invalid as soon as a new edition has been issued. Please check with Andura Coatings that you have the latest edition.

Andura Coatings Limited  
20 Murdock Road  
Bicester  
Oxon  
OX26 4PP

Telephone: 01869 240374  
Fax: 01869 240375  
Web: [www.andura.com](http://www.andura.com)  
e-mail: [info@andura.co.uk](mailto:info@andura.co.uk)

*Issue No 11/05*



Certificate No. FM 14830

*Page 2 of 2*