

ClearGard

1. Product identification and company details

Product name: Clear Gard

Intended use: Hydrophobic treatment of external masonry surfaces

Company address: Andura Coatings, 20 Murdock Road, Bicester, Oxon.
OX26 4PP

Emergency telephone no. 01869 240374 (not 24 hour)

2. Hazard identification

label elements

No signal word

Not classified

Precautionary statements

P102 – Keep out of reach of children

P101 – If medical advice is needed, have product container or label at hand.

P262 – Do not get in eyes, on skin, or on clothing.

Supplementary information:

EUH 208 – Contain chloromethyl isothiazolinone/methyl isothiazolinone. May produce an allergic reaction

EUH066 - Repeated exposure may cause skin dryness and cracking

3. Composition / Information On Ingredients

substances which present a health or environmental hazard within the meaning of the clp regulations or which are assigned occupational exposure values.

Name	Conc.Range	Symbol	Hazard statement	EC No
Mixture of aliphatic hydrocarbons	>40 - <50		Asp. Tox 1; H304 EUH066	265-149-8
Aliphatic and naphthenic hydrocarbons	>10 - <15		Asp. Tox 1; H304 EUH066	265-150-3

*see section16 for full text

4. First aid measures

General:

In case of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation:

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or has stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice

Eye Contact:

Remove contact lenses. Irrigate copiously with clean, fresh water for at least ten minutes, holding the eyes apart, and seek medical advice.

Skin Contact:

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleanser. Do NOT use solvent or thinners.

Ingestion:

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do not induce vomiting.

5. Fire-Fighting Measures

Extinguishing media: Recommended: alcohol resistant foam, CO₂, powder, water spray/mist.
Not to be used: water jet.

Recommendations: Fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Appropriate self contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow water run-off from fire fighting to enter drains or water courses.

6. Accidental release measures

Exclude sources of ignition and ventilate the area. Exclude not essential personnel. Avoid breathing vapours. Refer to protective measures listed in section 7 and 8. Contain the spillage with non combustible absorbent materials eg. Sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with the waste regulations (see section 13). Do not allow to enter drains or water-courses. Clean, preferably with detergent: avoid use of solvents. If the product enters drains or sewers, immediately contact the local water company; in case of contamination of streams, rivers or lakes, the relevant environment agency.

7. Handling and storage

Handling

Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Non sparking tools should be used.

Avoid skin and eye contact. Avoid the inhalation of vapour and mist.

For Occupational Exposure Control measures, see section 8.

Never use pressure to empty: the container is not a pressure vessel. Always use containers the same as the supply container.

(The Manual Handling Operations Regulations may apply to the handling of containers of this product)

Storage

Observe label precautions. Store between 5deg and 25deg C in a dry, well ventilated place away from sources of heat, ignition or direct sunlight.

No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage.

Store separately from oxidising agents and strongly alkaline or acidic materials.

8. Exposure controls/personal protection

Exposure controls

Provide adequate ventilation. Where reasonably practical, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of solvent vapour and/or particulates below the relevant occupational Exposure Limit Values, suitable respiratory protection must be worn.

Exposure Limit Values

Maximum airborne concentrations at the workplace:

Components with critical values that require monitoring in the workplace.

Substance	STD	TWA	STEL	Notations
		ppm mg.m	ppm mg.mm	
Ethanol		1000 1920 (OEL)		

WEL = Workplace exposure limit

(1) Long term exposure limit – 8 hour time weighted average.

(2) Short term exposure limit – 15 minute reference period.

Occupational Exposure Controls

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

Respiratory Protection.

Air fed respiratory equipment should be worn when this product is sprayed if the exposure of the sprayer or other people nearby cannot be controlled below the occupational Exposure Limit Values and engineering controls and methods cannot reasonably be improved.

Hand Protection.

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement, must be followed.

Barrier creams may help to protect exposed skin, but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

Eye Protection

Eye protection designed to protect against liquid splashes should be worn.

Skin Protection.

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleanser.

Regular skin inspection of users of this product is recommended.

Always wash your hands before eating, drinking, smoking or using the toilet.

Environmental exposure control.

See section 12 for detailed information.

9. Physical and chemical properties

Physical state: Paste

Flash Point: 75°C

Specific Gravity: Approx. 0.84

Vapour density: No data

Lower explosion limit: Approx. 0.6 vol %

Solubility in water: emulsifiable

10. Stability and reactivity

Stable under normal storage and handling conditions (see section 7). In a fire, hazardous decomposition products such as smoke, carbon monoxide, and oxides of nitrogen may be produced. Keep away from oxidising agent and strongly alkaline or acidic materials to prevent the possibility of exothermic reactions.

11. Toxicological information.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhoea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

12. Ecological information.

12.1 Toxicity

Conclusion/summary: Not available

12.2 Persistence and degradability

Conclusion/summary: Not available

12.3 Bioaccumulative effect

Not available

12.4 Mobility in soil

Soil/water partition coefficient: Not available

Mobility: Not available

12.5 Results of PBT and vPvB assessment

PBT: Not available

vPvB: Not available

12.6 Other adverse effects

No known adverse effects or critical hazards

The product should not be allowed to enter drains or water courses or to be deposited where it can affect ground or surface waters.

14. Transport information

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure persons transporting the product know what to do in the event of an accident or spillage.

This product is not classified as dangerous for carriage.

15. Regulatory information.

15.1

Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

None of the components is listed

15.2

Chemical Safety Assessment: No Chemical Safety Assessment has been carried out.

Substances of very high concern: None of the components are listed

VOC for Ready-for-Use Mixture: IIA/i. One pack performance coatings. EU limit values: 500g/l (2010.) This product contains a maximum of 500 g/l VOC.

16. Other information

Text of the H phrases listed in Section 2

Asp. Tox. 1; Aspiration hazard Category 1; May be fatal if swallowed and enters airways

H304

EUH066 Repeated exposure may cause skin dryness and cracking

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet is based on the present state of knowledge and on current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and advice can be found in the latest amendments of:

The Control of Substances Hazardous to Health Regulations 2002[SI2002:2677], The Stationery Office
COSHH Essentials: easy steps to control chemicals [HSG 193], HSE Books. Details of Control Guidance Sheets, which may be relevant to the particular conditions of use, can also be found in this publication.

The Manual Handling Operations Regulations 1992 [SI 1992:2793], The Stationery Office
Chemical Warehousing: Storage of Flammable Liquids in Containers [HSG51], HSE Books

Storage of Packaged Dangerous Substances [HSG71], HSE Books

The Environmental Protection (Duty of Care) Regulations 1992 [SI 1992:2839], The Stationery Office

A Guide to Working with Solvents [INDG 272], HSE Books

conforms to regulation (ec) no. 1907/2006 (reach), annex ii, as amended by uk reach regulation si 2019/758